

② LEVEL II

NRL Memorandum Report 4354

AD A106229

Non-Linear Analysis of the Free Electron Lasers Utilizing a Linear Wiggler Field

CHA-MEI TANG AND P. SPRANGLE

*Plasma Theory Branch
Plasma Physics Division*

DTIC
ELECTE
OCT 27 1981
S B D

October 19, 1981

This research was supported by the Defense Advanced Research Projects Agency under contract no. 3817.



NAVAL RESEARCH LABORATORY
Washington, D.C.

Approved for public release; distribution unlimited.

81 10 27 334

DTIC FILE COPY

Memorandum rept.

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER NRL Memorandum Report/4354	2. GOVT ACCESSION NO. AD-A106	3. RECIPIENT'S CATALOG NUMBER 229
4. TITLE (and Subtitle) NON-LINEAR ANALYSIS OF THE FREE ELECTRON LASERS UTILIZING A LINEAR WIGGLER FIELD		5. TYPE OF REPORT & PERIOD COVERED Interim report on a continuing NRL problem.
7. AUTHOR(s) Cha-Mei Tang and P. Sprangle		6. PERFORMING ORG. REPORT NUMBER
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Research Laboratory Washington, DC 20375		8. CONTRACT OR GRANT NUMBER(s)
11. CONTROLLING OFFICE NAME AND ADDRESS Defense Advanced Research Projects Agency Arlington, VA 22209		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62301E; 47-0867-0-1
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		12. REPORT DATE October 19, 1981
		13. NUMBER OF PAGES 34
		15. SECURITY CLASS. (of this report) UNCLASSIFIED
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Free electron laser (FEL)		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A one-dimensional steady state FEL amplifier, utilizing a linearly polarized magnetic wiggler field, is analyzed in the linear and non-linear operating regimes. Our formulation of the FEL problem includes all the efficiency enhancements schemes, electron beam thermal effects and collective effects, i.e., space charge waves. The axial electron velocity, due to a linearly polarized wiggler field, has a spatially oscillatory component. It is shown that this axial velocity jiggle does not result in phase incoherence between the electrons and the ponderomotive wave. The axial velocity jiggle is explicitly incorporated		

(Continues)

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE
S/N 0102-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

251950

20. ABSTRACT (Continued)

into our analytical model. The inclusion of the electron jiggle velocity is shown to have a quantitative effect on the non-linear wave particle dynamics. The electron trapping potential associated with the ponderomotive wave is also derived. Finally, a number of numerical examples pertinent to the design of a 10 μm FEL amplifier are presented.

micron

A

CONTENTS

I. INTRODUCTION	1
II. PHASE COHERENCE	2
III. LINEAR AND NON-LINEAR THEORY	5
a. Non-Linear Self-Consistent Formulation	5
b. Trapping Potential	10
c. Linear Gain	10
IV. ILLUSTRATIVE EXAMPLE OF A 10 μ m FEL	12
ACKNOWLEDGMENTS	15
REFERENCES	16

DTIC
ELECTE
S **D**
OCT 27 1981
B

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A	

NON-LINEAR ANALYSIS OF THE FREE ELECTRON LASERS UTILIZING A LINEAR WIGGLER FIELD

I. INTRODUCTION

Free electron lasers (FELs) based on stimulated scattering from relativistic electron beams show great potential for becoming a new class of efficient devices capable of generating intense levels of coherent radiation. This class of FELs is characterized by a pump or wiggler field which is typically a spatially periodic magnetic field.

The magnetic wiggler field can be either linearly or circularly polarized. A circularly polarized wiggler is somewhat simpler to analyze because the axial particle velocity, for a fixed amplitude and period wiggler, is constant (independent of axial position). A linearly polarized wiggler, on the other hand, introduces a spatially oscillating term in the axial particle velocity. To our knowledge previous FEL analyses⁽¹⁻³²⁾ have either taken the wiggler to be circularly polarized or have neglected the spatially oscillating part of the axial particle velocity with a linearly polarized wiggler.

Many of the future FEL experiments will employ a linearly polarized magnetic wiggler field. There are a number of practical advantages to this type of wiggler as opposed to a circularly polarized wiggler. These advantages are: i) relative simplicity of construction (which includes axial variation of the amplitude and period of the wiggler), ii) somewhat higher field amplitudes can be obtained and, iii) it is easier to obtain a linearly polarized radiation source for amplification.

Manuscript submitted August 24, 1981.

II. PHASE COHERENCE

In this paper we analyze the FEL in the steady state amplifying configuration. Our model for the FEL consists of a one dimensional relativistic electron beam propagating through a linearly polarized spatially periodic magnetic wiggler field $B_w(z)$, as shown in Fig. 1. The vector potential associated with the linearly polarized magnetic pump is

$$\underline{A}_w(z) = A_w(z) \sin \int_0^z k_w(z') dz' \hat{e}_y, \quad (1)$$

where the amplitude $A_w(z)$ and period $\lambda_w(z) = 2\pi/k_w(z)$ are slowly varying, known functions of z . The general temporal steady state radiation field and electrostatic (Coulomb) field excited by the interaction of the electron beam and wiggler field are respectively given by

$$\underline{A}(z,t) = A(z) \sin \left(\int_0^z k(z') dz' - \omega t \right) \hat{e}_y, \quad (2a)$$

and

$$\begin{aligned} \phi(z,t) = & \phi_1(z) \cos \left(\int_0^z (k(z') + k_w(z')) dz' - \omega t \right) \\ & + \phi_2(z) \sin \left(\int_0^z (k(z') + k_w(z')) dz' - \omega t \right), \end{aligned} \quad (2b)$$

where A, ϕ_1, ϕ_2 , and k are assumed to be slowly varying functions of z compared to the radiation wavelength. Even for highly efficient FELs the radiation field is typically much less than the pump field, i.e., $|A| \ll |A_w|$. In this section we will consider some of the characteristics of a FEL with a linearly polarized magnetic pump field and take A_w, k_w and k to be independent of axial position.

In the presence of only the wiggler field the electron velocity is

$$v_x = 0 ,$$

$$v_y = v_{0\perp} \sin k_w z , \quad (3a-c)$$

$$v_z = v_{0z} + \frac{v_{0\perp}^2}{4v_0} \cos 2 k_w z ,$$

where $v_{0\perp} = |e|A_w/(\gamma_0 m_0 c)$ is the magnitude of the transverse wiggler velocity, $v_{0z} = v_0 - v_{0\perp}^2/4v_0$ is the average axial velocity, v_0 is the magnitude of the total velocity, i.e., $\gamma_0 = (1 - v_0^2/c^2)^{-1/2}$. For the present it is sufficient to say that the frequency of the radiation field is such that phase coherence exists between the ponderomotive wave and the axial particle motion. That is, the axial phase velocity of the ponderomotive wave and the axial particle velocity must be matched so that an exchange of energy between the particles and radiation field can take place. The phase velocity of the ponderomotive wave is $v_{ph} = \omega/(k + k_w)$. By taking $k = \omega/c$ and equating v_{ph} to the average axial particle velocity v_{0z} , we find that the radiation frequency is given by

$$\omega = ck = (1 + \beta_0) \gamma_{zo}^2 v_{0z} k_w , \quad (4)$$

where $\gamma_{zo}^2 = \gamma_0^2/(1 + \beta_{0\perp}^2 \gamma_0^2/2)$ is the effective axial gamma factor,

$\beta_{0\perp} = v_{0\perp}/c$. It will now be shown that the spatially oscillatory part of the axial particle velocity, the second term of (3c), does not lead to phase incoherence regardless of the magnitude or wavelength of the wiggler field. The condition for phase coherence is

$$(k + k_w) \delta z_{os} \ll \pi/2 , \quad (5)$$

where $\delta z_{os} = \beta_{o\perp}^2 / 8k_w$ is the amplitude of the axial particle displacement associated with the spatially oscillatory part of the axial particle velocity. Using (4) we find that

$$(k + k_w) \delta z_{os} = \frac{1}{2} (1 - (1 + \beta_{o\perp}^2 \gamma_o^2 / 2)^{-1}) < \frac{1}{2} , \quad (6)$$

and is always less than 1/2 and typically $\approx 1/4$. Hence, the phase coherence condition in (5) is always satisfied even for arbitrarily strong pump fields. Therefore, the oscillatory part of the axial particle velocity in a linearly polarized pump can never result in phase incoherence.

III. LINEAR AND NON-LINEAR THEORY

a. Non-Linear Self-Consistent Formulation

In this section we formulate the 1-D non-linear theory of the FEL for a linearly polarized wiggler field. We include in our formulation of the problem: i) a spatially varying wiggler amplitude and period, ii) space charge fields, and iii) a D.C. accelerating field $E_{ac}(z) = -\partial\phi_{ac}/\partial z \hat{e}_z$. The present formulation is similar to our previous treatment of the circularly polarized wiggler problem.⁽²⁶⁾ We will show later that the applications of the D.C. accelerating field can modify the phase of the particles resulting in enhanced efficiency.⁽³³⁻³⁶⁾ This method is equivalent to schemes in which the pump amplitude and/or period is varied as a function of z (26-28, 31).

The wave equations for A and ϕ are

$$\left(\frac{\partial^2}{\partial z^2} - \frac{1}{c^2} \frac{\partial^2}{\partial t^2}\right) A_y(z,t) = -\frac{4\pi}{c} J_y(z,t) , \quad (7a)$$

and

$$\frac{\partial^2 \phi(z,t)}{\partial z \partial t} = 4\pi J_z(z,t) . \quad (7b)$$

The driving currents, J_y and J_z , are given by

$$J(z,t) = -|e| \int \frac{\underline{p}}{\gamma(\underline{p})m_0} f(z,\underline{p},t) d^3p . \quad (8)$$

The thermal electron distribution function can be expressed in the following form

$$f(z, \underline{p}, t) = n_0 \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} \frac{u_{z0} g_0(u_{z0})}{\gamma_0(u_{z0})} \delta(z - \tilde{z}(t_0, u_{z0}, t)) \quad (9)$$

$$\delta(p_y - \tilde{p}_y(t_0, u_{z0}, t)) \delta(p_z - \tilde{p}_z(t_0, u_{z0}, t)) dt_0 du_{z0},$$

where n_0 is the uniform particle density for $z \leq 0$, which is to the left of the interaction region and hence outside of the wiggler field, $u_{z0} = p_{z0}/m_0$, p_{z0} is the axial electron momentum for $z \leq 0$, $g_0(u_{z0})$ is the distribution function associated with the initial spread in axial electron momentum, $\tilde{z}(t_0, u_{z0}, t)$ is the axial position at time t of the particle which crossed the $z = 0$ plane at time t_0 with axial momentum p_{z0} and $\tilde{\underline{p}}(t_0, u_{z0}, t)$ is the momentum vector at time t of the particle which crossed the $z = 0$ plane at time t_0 with axial momentum p_{z0} . Substituting (9) into (8) and carrying out the integration over momentum, the driving current becomes

$$\underline{J}(z, t) = -|e|n_0 \int_{-\infty}^{\infty} \int_{-\infty}^{\infty} \frac{u_{z0}}{\gamma_0(u_{z0})} g_0(u_{z0}) \frac{\tilde{\underline{p}}(t_0, u_{z0}, t)}{\tilde{p}_z(t_0, u_{z0}, t)} \quad (10)$$

$$\delta(t - \tau(t_0, u_{z0}, z)) dt_0 du_{z0},$$

where

$$\tau(t_0, u_{z0}, z) = t_0 + \int_0^z \frac{dz'}{\tilde{v}_z(t_0, u_{z0}, z')},$$

is the time it takes a particle to travel to position z if it crossed the $z = 0$ plane at time t_0 with momentum $p_{z0} = m_0 u_{z0}$. Note that $\tilde{v}_z = \tilde{p}_z/\tilde{\gamma}m_0$ is the axial velocity of the particle with initial conditions t_0, u_{z0} .

Following the method presented in Ref. (26), we obtain the equations governing the amplitude and wavenumber of the radiation field and space charge field. Substituting (10) into (7), and multiplying the electromagnetic wave equation by $\frac{\sin}{\cos} \left(\int_0^z (k(z')) dz' - \omega t \right)$ and the electro-static wave equation by $\frac{\sin}{\cos} \left(\int_0^z (k(z') + k_w(z')) dz' - \omega t \right)$ and integrating over one time period, we obtain the following equations for $A(z)$, $k(z)$, $\phi_1(z)$, and $\phi_2(z)$,

$$\left(\frac{\omega}{c} - k(z) \right) A(z) = - \frac{1}{2} \frac{\omega_b^2}{c^2} \frac{1}{\omega} \int_{-\infty}^{\infty} \frac{u_{zo} g_o(u_{zo})}{\gamma_o(u_{zo})} \left[A_w(z) \left\langle \frac{\cos \tilde{\psi}(t_o, u_{zo}, z)}{\tilde{\gamma}(t_o, u_{zo}, z)} \right\rangle + A(z) \right] du_{zo}, \quad (11a)$$

$$k^{1/2}(z) \frac{\partial}{\partial z} \left(A(z) k^{1/2}(z) \right) = \frac{1}{2} \frac{\omega_b^2}{c^2} \frac{1}{c} \int_{-\infty}^{\infty} \frac{u_{zo} g_o(u_{zo})}{\gamma_o(u_{zo})} A_w(z) \left\langle \frac{\sin \tilde{\psi}(t_o, u_{zo}, z)}{\tilde{\gamma}(t_o, u_{zo}, z)} \right\rangle du_{zo}, \quad (11b)$$

$$\phi_1(z) = - \frac{\omega_b^2}{c^2} \frac{c^2}{\omega^2} \frac{2m_o c}{|e|} \int_{-\infty}^{\infty} \frac{u_{zo} g_o(u_{zo})}{\gamma_o(u_{zo})} \langle \cos \tilde{\psi}(t_o, u_{zo}, z) \rangle du_{zo}, \quad (11c)$$

$$\phi_2(z) = - \frac{\omega_b^2}{c^2} \frac{c^2}{\omega^2} \frac{2m_o c}{|e|} \int_{-\infty}^{\infty} \frac{u_{zo} g_o(u_{zo})}{\gamma_o(u_{zo})} \langle \sin \tilde{\psi}(t_o, u_{zo}, z) \rangle du_{zo}, \quad (11d)$$

where $\omega_b = (4\pi |e|^2 n_o / m_o)^{1/2}$,

$$\langle \text{---} \rangle = \frac{\omega}{2\pi} \int_0^{2\pi/\omega} dt_0 \langle \text{---} \rangle \text{ and } \tilde{\psi}(t_0, u_{z0}, z) = \int_0^z \left((k(z') + k_w(z')) - \frac{\omega}{v_z} \right) dz' - \omega t_0$$

is the phase of the electron with respect to the beat wave (ponderomotive wave). If the electron beam can be considered to have negligible spread in axial momentum, upon entering the interaction region, we may replace $g_0(u_{oz})$ with a delta function, and carry out the integration over u_{oz} .

To complete the formulation of the FEL problem we require an equation describing the evolution of the phase $\tilde{\psi}(t_0, u_{z0}, z)$. To obtain this equation we first note that the y component of the particle's canonical momentum is a constant of motion. In terms of the Lagrangian independent variables z , t_0 and u_{z0} the axial particle momentum is given by

$$\begin{aligned} \frac{d\tilde{p}_z}{dz} = & \frac{-|e|^2}{2 m_0 c^2 \tilde{v}_z \tilde{\gamma}^2} \left[\frac{\partial}{\partial z} (\tilde{A}_w(z) + \tilde{A}(z, t = \tau))^2 \right. \\ & \left. - 2\tilde{\gamma} \frac{m_0 c^2}{|e|} \frac{\partial \phi(z, t = \tau)}{\partial z} \right] - \frac{|e|}{\tilde{v}_z} E_{ac}(z), \end{aligned} \quad (12)$$

where $\tilde{p}_z = \tilde{p}_z(t_0, u_{z0}, t = \tau(t_0, u_{z0}, z)) = \tilde{\gamma} \tilde{v}_z m_0$. Equation (12) can be put into a more convenient and illuminating form by dropping terms which are not synchronous with the ponderomotive wave, using the well satisfied inequality $|A| \ll |A_w|$ and assuming highly relativistic axial particle velocities. With these assumptions, together with the definition of the relative phase $\tilde{\psi}$, equation (12) takes the form of a generalized pendulum like equation

$$\begin{aligned}
\frac{\partial^2 \tilde{\psi}}{\partial z^2} = & \frac{\partial k_w}{\partial z} - \frac{1}{4} \left(\frac{|e|}{\tilde{\gamma}_m c^2} \right)^2 \frac{\omega}{c} \frac{\partial A_w^2}{\partial z} + \frac{|e| \omega/c}{m_0 c^2 \tilde{\gamma} \tilde{\gamma}_z^2} \frac{\partial \phi_{ac}}{\partial z} \\
& + \frac{\partial k}{\partial z} - \left(\frac{|e|}{\tilde{\gamma}_m c^2} \right)^2 k k_w \left(A_w A \sin \tilde{\psi} + \frac{A_w^2}{2} \sin \left(2 \int_0^z k_w dz' \right) \right) \\
& + \frac{2\omega_b^2/c^2}{\tilde{\gamma} \tilde{\gamma}_z^2} \left(\langle \cos \tilde{\psi} \rangle \sin \tilde{\psi} - \langle \sin \tilde{\psi} \rangle \cos \tilde{\psi} \right), \quad (13)
\end{aligned}$$

where $\tilde{\gamma}_z = (1 - \tilde{v}_z^2/c^2)^{-1/2}$. In obtaining (13) we have assumed that all the particles have the same initial axial momentum, i.e., cold beam limit. The various terms affecting the phase in the generalized pendulum-like equation can now be distinguished. The first three terms represent the various efficiency enhancement methods available in the FEL. They include: i) tapering the wiggler wavelength, ii) tapering the wiggler amplitude and iii) D.C. accelerating potential. The equivalence of these schemes is evident. The fourth term is due to the self-consistent spatial variation of the radiation wavelength and can usually be neglected. The fifth and sixth terms represent: i) the ponderomotive wave due to the beating of the wiggler and radiation field and ii) the ponderomotive static wave due to the beating of the wiggler field with itself. If a circularly polarized wiggler field were chosen instead of a linearly polarized wiggler, the sixth term would not appear. The final term denotes the effects of space charge (collective) waves on the phase. The application of a D.C. accelerating potential can be an important method for enhancing the FEL's efficiency. If instead of a static magnetic wiggler field an electromagnetic wiggler is employed as a pump source, control of the wiggler amplitude or wavelength is not possible in a simple way. Application of a D.C. accelerating field is the most straightforward method for efficiency enhancement.

b. Trapping Potential.

One promising approach that can be taken to enhance efficiency is to initially trap a large fraction of the particles in the ponderomotive potential wells and adiabatically extract kinetic energy from the particles. To trap a substantial fraction of the electrons the trapping potential must be large or at least comparable to the initial spread in particle energy. This implies that a rather large amplitude radiation field must exist at the input to the interaction region. Using (14) it can be shown that the full trapping potential is given by $|e|\phi_{\text{trap}}/(\gamma_0 m_0 c^2) = (\frac{\Delta\gamma}{\gamma_0})_{\text{trap}} = 2\sqrt{2} \gamma_{z0} \beta_{0\perp} (A/A_w)^2$ where A is the radiation vector potential amplitude.

c. Linear Gain.

As a special case of (13) we consider the low gain, constant wiggler regime without space charge effects. Equation (13) reduces to the well known pendulum equation

$$\frac{d^2\tilde{\psi}}{dz^2} = - \left(\frac{|e|\hbar}{\gamma_0 m_0 c^2} \right)^2 k k_w (A_w A \sin \tilde{\psi} + \frac{A_w^2}{2} \sin(2 k_w z)) , \quad (14)$$

where the radiation wavelength has also been taken as constant, i.e.,

$\partial k/\partial z = 0$. Using Eq. (11b) and (14) the small signal gain, i.e.,

$G = (A(z) - A(0))/A(0)$ for a linearly polarized wiggler field, can be shown to be given by

$$G = -(1/16) \xi^2 \beta_{0\perp}^2 (k_w z)^3 \partial(\sin \theta/\theta)^2/\partial \theta, \quad (15)$$

where $\theta = \mu z/2$, $\mu = (k + k_w) - \omega/v_{z0} = k_w(\omega_0 - \omega)/\omega_0$, $\xi = \omega_b/\sqrt{\gamma_0} c k_w$. It is worth noting that the gain for a linearly polarized wiggler field is less

than that for a circularly polarized wiggler by a factor of two. Except for this factor the gain expressions are identical. That is, the small signal gain (10) for a linearly polarized wiggler and for a circularly polarized wiggler (15,24-25,27) are identical if the amplitude of the latter is reduced by $\sqrt{2}$, i.e., if the amplitude of the circularly polarized wiggler is equal to the rms value of the amplitude of the linearly polarized wiggler.

The linear gain expression Eq. (15) does not take saturation effects into account. When the frequency mismatch is small,

$$0 < \frac{-\Delta\omega}{\omega_0} < \frac{\Delta\gamma}{\gamma_0} \bigg|_{\text{trap}}, \quad (16)$$

some particles are initially trapped, and the trapped particles cause saturation to occur within a short interaction length. Thus, the linear gain expression Eq. (15) should be used with discretion.

In what follows, the efficiency will be defined as the ratio of the electromagnetic energy flux increase to the initial electron kinetic energy flux

$$\eta(z) = \frac{1}{2} \left(\frac{|e|}{m_0 c} \right)^2 \frac{\omega_r}{\omega_b} \left(\frac{k(z)A^2(z) - k(0)A^2(0)}{v_{z0}(\gamma_0 - 1)} \right). \quad (17)$$

IV. ILLUSTRATIVE EXAMPLE OF A 10 μ m FEL

We now present a number of illustrative examples of an FEL utilizing a linearly polarized magnetic pump. In our examples we have chosen a 25 MeV electron beam ($\gamma_0 = 50$), electron beam particle density of $n_0 = 5 \times 10^{10} \text{ cm}^{-3}$, a magnetic wiggler field amplitude of $B_0 = 5 \text{ kG}$ and wavelength of $\lambda_w = 2.8 \text{ cm}$. For these parameters, $A_w = 2.23 \times 10^3 \text{ stat volts}$, $k_w = 2.24 \text{ cm}^{-1}$, $\beta_{0z} = 2.61 \times 10^{-2}$, $\xi = 2.65 \times 10^{-2}$ and $\gamma_{z0} = 36.7$. The radiation wavelength is very nearly 10 μ m. As the input radiation source, we chose a high power CO₂ laser with a power flux of $5 \times 10^7 \text{ W/cm}^2$, $A(0) = 0.1 \text{ stat volts}$. Using the expression for the trapping potential we find that, with the above parameters, $\sim 2\%$ energy spread on the electron beam can be tolerated and substantial fraction of the electrons can still be trapped. In the following examples, Eqs. (11a-d) and (13) are solved numerically. Figure 2 shows the efficiency, for a constant parameter wiggler, as a function of axial position for $\Delta\omega/\omega_0 = (\omega - \omega_0)/\omega_0 = -1.25 \times 10^{-2}$ where $\omega_0 = 2 \gamma_z^2 c k_w$. The radiation field saturates at $z = 70 \lambda_w$ with a net gain of 0.4 and efficiency of 0.7%. Figure 3 shows the linear gain as a function of frequency mismatch, $\Delta\omega/\omega_0$. The dotted curve is the exact gain curve at $z = 30 \lambda_w$ in the linear regime of the interaction. The solid curve is the gain obtained from Eq. (15) evaluated at $z = 30 \lambda_w$.

In Fig. 4 the gain as a function of axial distance is shown for a frequency close to resonance, $\Delta\omega/\omega_0 = -7 \times 10^{-3}$. The dotted curve is the exact gain obtained from the self-consistent non-linear equations, while the solid curve is the linear gain from Eq. (15). Since $\left. \frac{\Delta\gamma}{\gamma_0} \right|_{\text{trap}} = 2 \times 10^{-2}$,

the inequality, Eq. (16), is satisfied, and particles are initially trapped. The trapped particles cause saturation to occur early in the interaction

region and saturation effects result in a decrease in the gain as compared to the linear gain expression. The linear gain expression does not take trapping into account and therefore, the linear gain expression in (15) should be used with discretion.

The next two figures depict the gain and efficiency as a function of frequency mismatch for linearly polarized and circularly polarized wiggler fields. In making this comparison the amplitude of the circularly polarized wiggler is set equal to the rms amplitude of the linearly polarized wiggler, i.e., $B_{\text{circular}} = B_{\text{linear}}/\sqrt{2}$. Also, the amplitude of the circularly polarized radiation field is set equal to the rms amplitude of the linearly polarized radiation field. The particle equations of motion for the two sets of field polarization are identical except for the longitudinally oscillating term (sixth term in Eq. (13)) which is associated with the linearly polarized wiggler field. Figure 5 is a plot of gain at saturation versus frequency mismatch for both types of wiggler polarizations. Figure 6 shows the efficiency curve versus frequency mismatch again for both polarizations of fields. Figures 5 and 6 demonstrate that the longitudinal jiggle term induced in a linear wiggler can have a quantitative effect on the non-linear FEL interaction.

As mentioned earlier, efficiency enhancement can be achieved using a number of schemes. The next figure shows an example in which the wiggler wavelength $\lambda_w(z)$ and amplitude $B_w(z)$ are varied in such a way that the product $\lambda_w B_w$ is held constant. ^(26-28,31) The frequency ω is chosen so that the ponderomotive wave is exactly resonant with the particles, i.e., $\Delta\omega = 0$. If none of the various efficiency enhancement schemes were employed, the gain would be zero. In Fig. 7, the tapering of the wiggler wavelength begins at the entrance of the interaction region. The period is changed from 2.8 cm at $z = 0$ to 2.66 cm at $z = 150$ $\lambda_w(0) = 420$ cm. The efficiency at the end of the interaction reached 1.15% as shown in Fig. 7. As seen

from this figure the efficiency can be much larger by extending the interaction length. By increasing the power flux of the input CO_2 laser signal or wiggler amplitude, the trapping potential can be increased, permitting a more rapid rate of decrease of the wiggler period.

ACKNOWLEDGMENTS

The authors appreciate useful discussions with I. B. Bernstein and W. M. Manheimer. The authors would also like to acknowledge the support for this work by DARPA under contract no. 3817.

REFERENCES

1. H. Motz, J. Appl. Physics. 22, 527 (1951).
2. J.M.J. Madey, J. Appl. Phys. 42, 1906 (1971).
3. R.B. Palmer, J. Appl. Phys. 43, 3014 (1972).
4. V.P. Sukhatme and P.W. Wolff, J. Appl. Phys. 44, 2331 (1973).
5. J.M.J. Madey, H.A. Schwettman and W.M. Fairbank, IEEE Trans. Nucl. Sci. 20, 980 (1973).
6. A.T. Lin and J.M. Dawson, Phys. Fluids 18, 201 (1975).
7. A. Hasegawa, K. Mima, P. Sprangle, H.H. Szu and V.L. Granatstein, Appl. Phys. Lett. 29, 542 (1976).
8. F.A. Hopf, P. Meystre, M.O. Scully and W.H. Louisell, Phys. Rev. Lett. 37, 1342 (1976).
9. F.A. Hopf, P. Meystre, M.O. Scully and W.H. Louisell, Optics Comm. 18, 413 (1976).
10. W.B. Colson, Phys. Lett. 59A, 187 (1976); W.B. Colson, Free Electron Laser Theory, Ph.D. Thesis, Stanford University (1977).
11. N.M. Kroll and W.A. McMullin, Phys. Rev. A17, 300 (1978).
12. P. Sprangle and V.L. Granatstein, Phys. Rev. A17, 1792 (1978).
13. J.M.J. Madey, D.A.G. Deacon, L.R. Elias, and T.I. Smith, Nuovo Cim. 51B, 53 (1979).
14. L.R. Elias, Phys. Rev. Lett. 42, 977 (1979).
15. W.H. Louisell, J.F. Lam, and D.A. Copeland, Phys. Rev. A18, 655 (1978).

16. P. Sprangle and V. L. Granatstein, Appl. Phys. Lett. 25, 377 (1974).
17. W. M. Manheimer and E. Ott, Phys. Fluids 17, 706 (1974).
18. V. I. Miroshnichenko, Sov. Tech. Phys. Lett. 1, 453, (1975).
19. G. Bekefi and R. E. Shefer, J. Appl. Phys. 50, 5158 (1979).
20. T. Kwan, J. M. Dawson and A. T. Lin, Phys. Fluids 20, 581 (1977).
21. V. L. Granatstein and P. Sprangle, IEEE Trans. MTT-25, 545 (1977).
22. A. Hasegawa, Bell System Tech. J. 57, 3069 (1978).
23. I. B. Bernstein and J. L. Hirshfield, Phys. Rev. Lett. 40, 761 (1978).
24. P. Sprangle, R. A. Smith and V. L. Granatstein, NRL Memo Report 3911 (1978). (Also published in Infrared and Millimeter Waves, Vol. 1, K. Button (ed.), Academic Press, 1979).
25. P. Sprangle and R. A. Smith, NRL Memo Report 4033 (1979), and Phys. Rev. A 21, 293 (1980).
26. P. Sprangle, Cha-Mei Tang and W. M. Manheimer, Phys. Rev. Lett. 43, 1932 (1979) and Phys Rev. A21, 302 (1980).
27. P. Sprangle and Cha-Mei Tang, Proc. of the Fourth Intl. Conf. on Infrared and Near-Millimeter Waves, page 98, Miami-Beach, 10-15 December 1979.
28. N. M. Kroll, P. Morton and M. N. Rosenbluth, JASON Tech. Report JSR-79-15 (1980).
29. A. T. Lin and J. M. Dawson, Phys. of Fluids, 23, 1224 (1980).
30. L. Friedland and J. L. Hirshfield, Phys. Rev. Lett. 44, 1456 (1980).

31. Free-Electron Generators of Coherent Radiation, Physics of Quantum Electronics, Vol.7, edited by S. F. Jacobs, H. S. Pilloff, M. Sargent, III, M. O. Scully and R. Spitzer, Addison-Wesley, Reading, MA. (1980).
32. R. C. Davidson, H. S. Uhm and R. E. Aamodt, MIT Plasma Fusion Center, MIT Report PFC/JA-80-4(1980).
33. Efficiency enhancement using a D.C. accelerating electric field have been discussed by i) P. Sprangle and Cha-Mei Tang, DARPA FEL Review, Arlington, VA., Dec. 3-4, 1979, ii) P. Sprangle and Cha-Mei Tang, DARPA/ONR/AFOSR FEL Program Review, LASL, April 24-25, 1980, and iii) Y. P. Ho, Y. C. Lee, and M. N. Rosenbluth, Sherwood meeting, Tuscon, Arizona, April 23-25, 1980.
34. P. Sprangle and Cha-Mei Tang, NRL Memo. Report 4280 (1980).
35. A.T. Lin, Report #PPG-456, Center of Plasma Physics and Fusion Energy, UCLA, Jan. (1980).
36. P. Sprangle and Cha-Mei Tang, AIAA 13th Fluid and Plasma Dynamics Conf. Paper No. AIAA-80-1404, Snowmass, Colorado, July 14-16, 1980.




Fig. 1 - Schematic of the free-electron laser model. The unmodulated electron beam enters the interaction region from the left. The wiggler field builds up adiabatically and reaches a constant amplitude for $z > 0$.




Fig. 2 - Efficiency versus normalized axial distance without efficiency enhancement for $\Delta\omega/\omega_0 = -1.25 \times 10^{-2}$




Fig. 3 - A comparison of the gain from linear gain expression (solid curve), and gain from non-linear calculation (dashed curve) as a function of frequency mismatch $\Delta\omega/\omega_0$ at $z = 30 l_w(0)$




Fig. 4 - A comparison of the gain from linear gain expression (solid curve) and gain from non-linear calculation (dashed curve) as a function of axial distance for a small frequency mismatch $\Delta\omega/\omega_0 = -7 \times 10^{-3}$




Fig. 5 - A comparison of gain at saturation using a linearly polarized wiggler (dashed curve) and circularly polarized wiggler (solid curve) versus frequency mismatch $-\Delta\omega/\omega_0$




Fig. 6 - A comparison of efficiency at saturation using a linearly polarized wiggler (dashed curve) and circularly polarized wiggler (solid curve) versus frequency mismatch $-\Delta\omega/\omega_0$




Fig. 7 - An example of efficiency enhancement by decreasing the magnetic wiggler period as shown for frequency that is on resonance. If the wiggler wavelength stayed constant, the saturation efficiency is approximately zero. The efficiency (solid curve) has increased to 1.15% at $z = 150 \lambda_w(0)$ with wiggler period $\lambda_w(z)/\lambda_w(0)$ (dashed curve) changing as shown.

DISTRIBUTION LIST*

Naval Research Laboratory
4555 Overlook Avenue, S.W.
Washington, D.C. 20375

Attn: Code 1000 - CAPT. E. E. Henifin
1001 - Dr. A. Berman
4700 - Dr. T. Coffey (26 copies)
4701 - Mr. J. Brown
4740 - Dr. V. L. Granatstein (20 copies)
4740 - Dr. R. K. Parker (20 copies)
4740 - Dr. K. R. Chu
4740 - Dr. C. W. Roberson
4790 - Dr. P. Sprangle (100 copies)
4790 - Dr. C. M. Tang
4790 - Dr. M. Lampe
4790 - Dr. W. M. Manheimer
6603S- Dr. W. W. Zachary
6650 - Dr. L. Cohen
6656 - Dr. N. Seeman
6850 - Dr. L. R. Whicker
6805 - Dr. S. Y. Ahn
6875 - Dr. R. Wagner

On Site Contractors:

Code 4740 - Dr. L. Barnett (B-K Dynamics)
4740 - Dr. D. Dialetis (SAI)
4740 - Dr. Y. Y. Lau (SAI)
4790 - Dr. A. T. Drobot (SAI)
4790 - Dr. J. Vomvoridis (JAYCOR)
4790 - Dr. H. Freund (SAI)

* Every name listed on distribution gets one copy except for those where extra copies are noted.

Dr. Tony Armstrong
SAI, Inc.
P. O. Box 2351
La Jolla, CA 92038

Dr. Robert Behringer
ONR
1030 E. Green
Pasadena, CA 91106

Dr. G. Bekefi (5 copies)
Massachusetts Institute of Technology
Bldg. 26
Cambridge, MA 02139

Dr. Arden Bement (2 copies)
Deputy Under Secretary of Defense
for R&AT
Room 3E114, The Pentagon
Washington, D.C. 20301

MAJ Rattig P. Benedict, USAF
DARPA/STO
1400 Wilson Boulevard
Arlington, VA 22209

Dr. T. Berlincourt
Code 420
Office of Naval Research
Arlington, VA 22217

Dr. I. B. Bernstein (2 copies)
Yale University
Mason Laboratory
400 Temple Street
New Haven, CT 06520

Dr. Charles Brau (2 copies)
Applied Photochemistry Division
Los Alamos National Scientific
Laboratory
P. O. Box 1663, M.S. - 817
Los Alamos, NM 87545

Dr. R. Briggs (L-71)
Lawrence Livermore National Lab.
P. O. Box 808
Livermore, CA 94550

Dr. Fred Burskirk
Physics Department
Naval Postgraduate School
Monterey, CA 93940

Dr. K. J. Button
Massachusetts Institute of Technology
Francis Bitter National Magnet Lab.
Cambridge, MA 02139

Dr. Gregory Canavan
Director, Office of Inertial Fusion
U. S. Department of Energy
M.S. C404
Washington, D.C. 20545

Prof. C. D. Cantrell
Center for Quantum Electronics
& Applications
The University of Texas at Dallas
P. O. Box 688
Richardson, TX 75080

Dr. Maria Caponi
TRW, Building R-1, Room 1070
One Space Park
Redondo Beach, CA 90278

Dr. J. Cary
Los Alamos National Scientific
Laboratory
MS 608
Los Alamos, NM 87545

Dr. Weng Chow
Optical Sciences Center
University of Arizona
Tucson, AZ 85721

Dr. Peter Clark
TRW, Building R-1, Room 1096
One Space Park
Redondo Beach, CA 90278

Dr. Robert Clark
P. O. Box 1925
Washington, D.C. 20013

Dr. William Colson
Quantum Institute
Univ. of California at Santa Barbara
Santa Barbara, CA 93106

Dr. William Condell
Code 421
Office of Naval Research
Arlington, VA 22217

Dr. Richard Cooper
Los Alamos National Scientific
Laboratory
P. O. Box 1663
Los Alamos, NM 87545

Cmdr. Robert Cronin
NFOIO Detachment, Suitland
4301 Suitland Road
Washington, D.C. 20390

Dr. R. Davidson (5 copies)
Plasma Fusion Center
Massachusetts Institute of
Technology
Cambridge, MA 02139

Dr. John Dawson (2 copies)
Physics Department
University of California
Los Angeles, CA 90024

Dr. David Deacon
Physics Department
Stanford University
Stanford, CA 94305

Defense Technical Information
Center (2 copies)
Cameron Station
5010 Duke Street
Alexandria, VA 22313

Dr. Francesco De Martini
Istituto de Fiscia
G. Marconi" Univ.
Piazzo delle Science, 5
ROMA00185 ITALY

Prof. P. Diamant
Columbia University
Dept. of Electrical Engineering
New York, NY 10027

Prof. J. J. Doucet (5 copies)
Ecole Polytechnique
91128 Palaiseau
Paris, France

Dr. John Elgin (2 copies)
Imperial College
Dept. of Physics (Optics)
London SWF, England

Dr. Luis R. Elias (2 copies)
Quantum Institute
University of California
Santa Barbara, CA 93106

Dr. David D. Elliott
SRI International
33 Ravenswood Avenue
Menlo Park, CA 94025

Dr. Jim Elliot (2 copies)
X-Division, M.S. 531
Los Alamos National Scientific
Laboratory
Los Alamos, NM 87545

Director (2 copies)
National Security Agency
Fort Meade, MD 20755
ATTN: Mr. Richard Foss, A42

Dr. Robert Fossum, Director
DARPA
1400 Wilson Boulevard
Arlington, VA 22209 (2 copies)

Dr. Edward A. Frieman
Director, Office of Energy Research
U. S. Department of Energy
M.S. 6E084
Washington, D.C. 20585

Dr. George Gamota (3 copies)
OUSDRE (R&AT)
Room 3D1067, The Pentagon
Washington, D.C. 20301

Dr. Richard L. Garwin
IBM, T. J. Watson Research Center
P. O. Box 218
Yorktown Heights, NY 10598

Dr. Edward T. Gerry, President
W. J. Schafer Associates, Inc.
1901 N. Fort Myer Drive
Arlington, VA 22209

Dr. Avraham Gover
Tel Aviv University
Fac. of Engineering
Tel Aviv, ISRAEL

Mr. Donald L. Haas, Director
DARPA/STO
1400 Wilson Boulevard
Arlington, VA 22209

Dr. P. Hammerling
La Jolla Institute
P. O. Box 1434
La Jolla, CA 92038

Director
National Security Agency
Fort Meade, MD 20755
ATTN: Mr. Thomas Handel, A243

Dr. William Happer
560 Riverside Drive
New York City, NY 10027

Dr. Robert J. Hermann
Assistant Secretary of the
Air Force (RD&L)
Room 4E856, The Pentagon
Washington, D.C. 20330

Dr. Rod Hiddleston
KMS Fusion
Ann Arbor, MI 48106

Dr. J. L. Hirshfield (2 copies)
Yale University
Mason Laboratory
400 Temple Street
New Haven, CT 06520

Dr. R. Hofland
Aerospace Corp.
P. O. Box 92957
Los Angeles, CA 90009

Dr. Fred Hopf
University of Arizona
Tucson, AZ 85721

Dr. Benjamin Huberman
Associate Director, OSTP
Room 476, Old Executive Office Bldg.
Washington, D.C. 20506

Dr. S. F. Jacobs
Optical Sciences Center
University of Arizona
Tucson, AZ 85721

Mr. Eugene Kopf
Principal Deputy Assistant
Secretary of the Air Force (RD&L)
Room 4E964, The Pentagon
Washington, D.C. 20330

Prof. N. M Kroll
La Jolla Institutes
P. O. Box 1434
La Jolla, CA 92038

Dr. Tom Kuper
Optical Sciences Center
University of Arizona
Tucson, AZ 85721

Dr. Thomas Kwan
Los Alamos National Scientific
Laboratory
MS608
Los Alamos, NM 87545

Dr. Willis Lamb
Optical Sciences Center
University of Arizona
Tucson, AZ 85721

Mr. Mike Lavan
BMDATC-0
ATTN: ATC-0
P. O. Box 1500
Huntsville, AL 35807

Dr. John D. Lawson (2 copies)
Rutherford High Energy Lab.
Chilton
Didcot, Oxon OX11 0OX
ENGLAND

Mr. Ray Leadabrand
SRI International
333 Ravenswood Avenue
Menlo Park, CA 94025

Mr. Barry Leven
NISC/Code 20
4301 Suitland Road
Washington, D.C. 20390

Dr. Donald M. LeVine (3 copies)
SRI International
1611 N. Kent Street
Arlington, VA 22209

Dr. Anthony T. Lin
University of California
Los Angeles, CA 90024

Director (2 copies)
National Security Agency
Fort Meade, MD 20755
ATTN: Mr. Robert Madden, R/SA

Dr. John Madey
Physics Department
Stanford University
Stanford, CA 94305

Dr. Joseph Mangano
DARPA
1400 Wilson Boulevard
Arlington, VA 22209

Dr. S. A. Mani
W. J. Schafer Associates, Inc.
10 Lakeside Office Park
Wakefield, MA 01880

Dr. Mike Mann
Hughes Aircraft Co.
Laser Systems Division
Culver City, CA 90230

Dr. T. C. Marshall
Applied Physics Department
Columbia University
New York, NY 10027

Mr. John Meson
DARPA
1400 Wilson Boulevard
Arlington, VA 22209

Dr. Pierre Meystre
Projektgruppe fur Laserforschung
Max Planck Gesellschaft
Garching, MUNICH WEST GERMANY

Dr. Gerald T. Moore
Optical Sciences Center
University of Arizona
Tucson, Az 85721

Dr. Philip Morton
Stanford Linear Accelerator Center
P. O. Box 4349
Stanford, CA 94305

Dr. Jesper Munch
TRW
One Space Park
Redondo Beach, CA 90278

Dr. George Neil
TRW
One Space Park
Redondo Beach, CA 90278

Dr. Kelvin Neil
Lawrence Livermore National Lab.
Code L-321, P. O. Box 808
Livermore, CA 94550

Dr. Brian Newnam
MS 564
Los Alamos National Scientific
Laboratory
P. O. Box 1663
Los Alamos, NM 87545

Dr. Milton L. Noble (2 copies)
General Electric Company
G. E. Electric Park
Syracuse, NY 13201

Prof. E. Ott (2 copies)
University of Maryland
Dept. of Physics
College Park, MD 20742

Dr. Richard H. Pantell
Stanford University
Stanford, CA 94305

Dr. Claudio Parazzoli
Hughes Aircraft Company
Building 6, MS/C-129
Centinela & Teale Streets
Culver City, CA 90230

Dr. Richard M. Patrick
AVCO Everett Research Lab., Inc.
2385 Revere Beach Parkway
Everett, MA 02149

Dr. Claudio Pellegrini
Brookhaven National Laboratory
Associated Universities, Inc.
Upton, L.I., NY 11973

The Honorable William Perry
Under Secretary of Defense (R&E)
Office of the Secretary of Defense
Room 3E1006, The Pentagon
Washington, D.C. 20301

Dr. Alan Pike
DARPA/STO
1400 Wilson Boulevard
Arlington, VA 22209

Dr. Hersch Pilloff
Code 421
Office of Naval Research
Arlington, VA 22217

Dr. Charles Planner
Rutherford High Energy Lab.
Chilton
Didcot, Oxon, OX11, OOX
ENGLAND

Dr. Michal Poole
Daresbury Nuclear Physics Lab.
Daresbury, Warrington
Cheshire WA4 4AD
ENGLAND

Dr. Don Prosnitz
Lawrence Livermore National Lab.
Livermore, CA 94550

Dr. D. A. Reilly
AVCO Everett Research Lab.
Everett, MA 02149

Dr. James P. Reilly
W. J. Schafer Associates, Inc.
10 Lakeside Office Park
Wakefield, MA 01880

Dr. A. Renieri
C.N.E.N.
Div. Nuove Attivita
Dentro di Frascati
Frascati, Rome
ITALY

Dr. Daniel N. Rogovin
SAI
P. O. Box 2351
La Jolla, CA 92038

Dr. Michael Rosenbluh
MIT - Magnet Laboratory
Cambridge, MA 02139

Dr. Marshall N. Rosenbluth
Institute for Advanced Study
Princeton, NJ 08540

Dr. Eugene Ruane (2 copies)
P. O. Box 1925
Washington, D.C. 20013

Dr. Antonio Sanchez
MIT/Lincoln Laboratory
Room B231
P. O. Box 73
Lexington, MA 02173

Dr. Aleksandr N. Sandalov
Department of Physics
Moscow University
MGU, Lenin Hills
Moscow, 117234, USSR

Prof. S. P. Schlesinger
Columbia University
Dept. of Electrical Engineering
New York, NY 10027

Dr. Howard Schlossberg
AFOSR
Bolling AFB
Washington, D.C. 20332

Dr. Stanley Schneider
Rotodyne Corporation
26628 Fond Du Lac Road
Palos Verdes Peninsula, CA 90274

Dr. Marlan O. Scully
Optical Science Center
University of Arizona
Tucson, AZ 85721

Dr. Steven Segel
KMS Fusion
3621 S. State Street
P. O. Box 1567
Ann Arbor, MI 48106

Dr. Robert Sepucha
DARPA/STO
1400 Wilson Boulevard
Arlington, VA 22209

Dr. A. M. Sessler
Lawrence Berkeley Laboratory
University of California
1 Cyclotron Road
Berkeley, CA 94720

Dr. Earl D. Shaw
Bell Labs
600 Mountain Avenue
Murray Hill, NJ 07974

Dr. Chan-Chin Shih
R&D Associates
P. O. Box 9695
Marina Del Rey, CA 92091

Dr. Jack Slater
Mathematical Sciences, NW
P. O. Box 1887
Bellevue, WA 98009

Dr. Kenneth Smith
Physical Dynamics, Inc.
P. O. Box 556
La Jolla, CA 92038

Mr. Todd Smith
Hansen Labs
Stanford University
Stanford, CA 94305

Dr. Joel A. Snow
Senior Technical Advisor
Office of Energy Research
U. S. Department of Energy, M.S. E084
Washington, D.C. 20585

Dr. Richard Spitzer
Stanford Linear Accelerator Center
P. O. Box 4347
Stanford, CA 94305

Mrs. Alma Spring
DARPA/Administration
1400 Wilson Boulevard
Arlington, VA 22209

DRI/MP Reports Area G037 (2 copies)
333 Ravenswood Avenue
Menlo Park, CA 94025
ATTN: D. Leitner

Dr. Abraham Szoke
Lawrence Livermore National Lab.
MS/L-470, P. O. Box 808
Livermore, CA 94550

Dr. Milan Tekula
AVCO Everett Research Lab.
2385 Revere Beach Parkway
Everett, MA 02149

Dr. John E. Walsh
Department of Physics
Dartmouth College
Hanover, NH 03755

Dr. Wasneski (2 copies)
Naval Air Systems Command
Department of the Navy
Washington, D.C. 20350

Ms. Bettie Wilcox
Lawrence Livermore National Lab.
ATTN: Tech. Info. Dept. 1-3
P. O. Box 808
Livermore, CA 94550

Dr. A. Yariv
California Institute of Tech.
Pasadena, CA 91125